

### Fibra product line

## StreetSiren Fibra

Wired siren with LED indication for indoor and outdoor use



StreetSiren Fibra is a device of the wired Fibra product line. Only accredited Ajax Systems partners can sell, install, and administer Fibra products.



# 4 missions, 1 device

- Alarm serves to scare off intruders and attract attention
- Security status indication notifies users about arming/ disarming the system and delays when entering/leaving
- Chime alerts users about the triggering of opening detectors when the system is disarmed
- After-alarm indication informs users and passing patrols when the system is triggered



### ((<u>)</u>) Adjustable alarms

- Group mode sets up a siren's response to changes in the security mode and alarms in its group
- Adjustable volume of alarm and notifications: from 85 dB to 113 dB
- Adjustable alarm duration: from 3 sec to 3 min



# Fibra

#### communication technology

- Up to 2,000 m of wired communication
- Data is encrypted throughout the transmission process
- Regular polling to display current device statuses
- One line for different types of devices



# Power supply

- Low power consumption of up to 0.37 W
- Pre-installed rechargeable battery powers the device
- Power supply calculator
- Power consumption stress test



# Sabotage resistance

- Tamper alarm
- Protection against short circuits
- Device authentication to prevent spoofing
- Holding screw to secure the device on SmartBracket
- Durable enclosure



## Easy installation

- Pairing with the system via QR code or line scanning
- SmartBracket mounting panel for installation without disassembling the siren enclosure
- Bubble level to check the inclination angle of the mounting during installation
- Remote control and configuration in Ajax apps

**Superior, Fibra**, and **Baseline** product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

Compliance	Alerts	Communication with hub	Features
EN 50131 (Grade 3)	Alarms	Fibra communication technology	Types of alerts
PD 6662:2017	Acoustic		Acoustic
INCERT	LED	Wired connection	LED
		U/UTP cat.5, $4 \times 2 \times 0.51$ with	
Compatibility	Delays when entering/leaving	a copper conductor	Alarm volume
	Acoustic		from 85 dB to 113 dB at a distance
Hubs		signal cable 4 × 0.22 with a copper	of 1 m
Hub Hybrid (2G),	Security mode change	conductor	Adjusted by a PRO or a user with
Hub Hybrid (4G)	Acoustic		admin rights in Ajax apps
	LED	Communication range	
		up to 2,000 m	Alarm duration
	Security status	With U/UTP cat.5, $4 \times 2 \times 0.51$ cable	from 3 sec to 3 min
	LED		Adjusted by a PRO or a user with admin rights in Ajax apps
	Chime		admininging in Ajax apps
	Acoustic		Piezoelectric buzzer frequency
	Acoustic		3.5 ± 0.5 kHz
	After-alarm indication		3.3 ± 0.3 KHZ
	LED		
Power supply	Installation	Enclosure	Complete set
Main	Operating temperature range	Colour	StreetSiren Fibra
24 V==, up to 100 μA	from -25 °C to +50 °C	black, white	SmartBracket mounting panel
From Fibra line			Installation kit
	Operating humidity	Dimensions	Quick start guide
Backup	up to 95%	198.5 × 198.5 × 59 mm	quiott start gards
LTO 18650, 1,500 mAh, 2.4 V==			
Up to 30 min of alarm signaling	Protection class	Weight	
after main power failure	IP54	516 g	
arter mani povici randic		J 1 5 9	
	Recommended installation height 2.5 m or higher	Tampering alarm	













For detailed information, scan the QR code or follow the link: