




## Industry Standard Dimensions






This battery contains a Positive Temperature Coefficient (PTC) safety device to limit current during short circuit conditions.

## Specifications

<b>Classification:</b>	"Lithium"
<b>Chemical System:</b>	Lithium / Manganese Dioxide (Li/MnO <sub>2</sub> )
<b>Designation:</b>	ANSI-5018LC, IEC-CR17345
<b>Nominal Voltage:</b>	3.0 Volts
<b>Storage Temp:</b>	-40°C to 60°C (-40°F to 140°F)
<b>Operating Temp:</b>	-40°C to 60°C (-40°F to 140°F)
<b>Typical Capacity:</b>	1500 mAh (to 2.0 volts) (Rated at 100 ohms at 21°C)
<b>Typical Weight:</b>	16.5 grams (0.58 oz.)
<b>Typical Volume:</b>	7.0 cubic centimeters (0.4 cubic inch)
<b>Max Discharge:</b>	1500 mA continuous (3500 mA pulse)
<b>Max Rev Current:</b>	2 $\mu$ A
<b>Typical Li Content:</b>	0.55 grams (0.019 oz.)
<b>UL Listed:</b>	MH29980

## Typical Discharge Characteristics



## Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication. Contents herein do not constitute a warranty and are for reference only.